


High-Security Two Door Controller

PDK's Red™ 2 controller includes built-in Ethernet connectivity and self-discovery, simplifying ip configuration and functionality. Communication plug-and-play connection options are added by purchasing a Red WiMAC™ wireless or PoE++ Module Kit. The Red 2 is equipped with OSDP functionality, an on-board power supply, and a fully-supervised power circuit that monitors input, output, battery voltage, and overall controller health.

Model

PN: R2



Optional Module Add-On Kits

WiMAC Wireless Module | PN: RMW

PoE++ Module | PN: RMPOE



Features



advanced security

ProdataKey Red™ products lead the industry in secure communication protocols. This includes OSDP, mobile, and encrypted credential communication.



self discoverable

The Red 2 will be automatically discovered by the Cloud Node when an Ethernet cable is connected; it is not necessary to enter the IP address; the device is self-discoverable.



power monitoring

Equipped with an on-board power supply, and a fully-supervised power circuit that monitors input, output, battery voltage, and overall controller health.



module kits

Additional WiMAC and PoE++ plug-and-play connection kits can be added by purchasing the respective wireless or PoE kit. Plug the module into the PDK Red 2 board, and it's ready to go.



plug'n'play connectivity

All PDK Red devices were designed to be plug n' play. That means they're easy to install right out of the box. It's simple to add any device, no matter how large the job is.



system scalability

Whether you need two doors or a thousand, the PDK Red 2 Controller gives you the flexibility to add more doors anytime, anywhere, on any device.

Specifications

Connections

Removable Screw-down Terminals
Built-in Power Supply
Industrial-grade 2A Form-C Relays (2)
Reader (2)
Input A (2)
Input B (2)

Communication Options

Ethernet
WiMAC™ Wireless (2.4 GHz/ 82.15.4
PoE++
Encryption: AES 128bit
Wireless Range: 1 Mile LoS, 450ft indoor
average

Environmental

Temperature: -4° ~ +14° F / -2° ~ +6° C
Humidity: - 95% relative humidity
non-condensing

Enclosure

Dimensions (W x H x D 1.4375" x 7.625" x 3"
Metal lockable security can (indoor use only)

Compliance

Conforms to UL 294



Manufacturer's Limited Warranty

One to five-year warranty against defects in materials and workmanship. For full details, visit www.prodatakey.com/warranty

Requirements

Power

12V-24V DC Input
14 VDC 2A 28 watt class 2 wall-wart power supply (Input sup-ply to the board)
Powers readers and other door hardware directly from the bus
* Battery not included, but a backup battery must be installed to comply with UL 294.