



L6

Wi-Fi 6 AX3000 Dual-Band Ceiling
Mount Access Point



DATASHEET

Overview	
Dimensions	Ø220 mm x 52.6 mm (Ø8.66 in. x 2.07 in.) (excluding the mounting bracket)
Weight	≤ 0.5 kg (1.10 lbs.) (without packaging materials) ≤ 0.7 kg (1.54 lbs.) (with packaging materials)
Wi-Fi Standards	IEEE 802.11 a/b/g/n/ac/ax
Spatial Streams	4
Coverage Area	145 m ² (1560.77 square ft.) Note: The data is obtained in an ideal environment without obstruction. The signal coverage radius depends on client performance and environmental interference.
Max. Client Count	64 (2.4 GHz) 512 (5 GHz) 512 (2.4 GHz and 5 GHz enabled)
Recommended number of associated wireless clients	<ul style="list-style-type: none"> • Support for IEEE 802.11ax and 160 MHz: 16 (2.4 GHz) 94 (5 GHz) 110 (2.4 GHz and 5 GHz enabled) • Support for IEEE 802.11ax and 80 MHz: 16 (2.4 GHz) 84 (5 GHz) 100 (2.4 GHz and 5 GHz enabled) • Support for IEEE 802.11ac: 16 (2.4 GHz) 64 (5 GHz) 80 (2.4 GHz and 5 GHz enabled)
Mounting	Ceiling Mount, Wall-mounted (Mounts Included)
Hardware	
Networking Interface	(1) 1GbE RJ45 port
Wi-Fi Protocols	2.4 GHz: IEEE 802.11 b/g/n/ax 5 GHz: IEEE 802.11 a/n/ac/ax
MIMO	2.4 GHz: 2 x 2 MU-MIMO 5 GHz: 2 x 2 MU-MIMO
Channel bandwidth	2.4 GHz: 20/40 MHz 5 GHz: 20/40/80/160 MHz
Throughput rate	2.4 GHz: 573 Mbps 5 GHz: 2401 Mbps
Antenna Gain	2.4 GHz: 3.53 dBi 5 GHz: 5.15 dBi
Max. Transmit Power	2.4 GHz: 28 dBm 5 GHz: 29.7 dBm



Power Consumption	≤ 18 W	
Power Method	PoE/PoE+ DC (12 V, 2A), DC Power Adapter Is Not Included	
Modulation	OFDM: BPSK @ 6/9 Mbps, QPSK @ 12/18 Mbps, 16-QAM @ 24 Mbps, and 64-QAM @ 48/54 Mbps DSSS: DBPSK @ 1 Mbps, DQPSK @ 2 Mbps, and CCK @ 5.5/11 Mbps MIMO-OFDM: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, and 1024-QAM OFDMA	
Receiver Sensitivity	11b: -91 dBm (1 Mbps), -88 dBm (5.5 Mbps), -85 dBm (11 Mbps) 11a/g: -89 dBm (6 Mbps), -80 dBm (24 Mbps), -76 dBm (36 Mbps), -71 dBm (54 Mbps) 11n: -83 dBm (MCS0), -65 dBm (MCS7), -83 dBm (MCS8), -65 dBm (MCS15) 11ac: 20 MHz: -83 dBm (MCS0), -57 dBm (MCS9) 11ac: 40 MHz: -79 dBm (MCS0), -57 dBm (MCS9) 11ac: 80 MHz: -76 dBm (MCS0), -51 dBm (MCS9) 11ac: 160 MHz: -76 dBm (MCS0), -50 dBm (MCS9) 11ax: 20 MHz: -85 dBm (MCS0), -58 dBm (MCS11) 11ax: 40 MHz: -82 dBm (MCS0), -54 dBm (MCS11) 11ax: 80 MHz: -79 dBm (MCS0), -52 dBm (MCS11) 11ax: 160 MHz: -76 dBm (MCS0), -49 dBm (MCS11)	
LED	1 x System LED indicator (blue)	
Button	1 x Factory reset	
Environment	Operating Temperature: 0°C to 40°C (32°F to 104°F) Storage Temperature: -40°C to +70°C (-40°F to +158°F) Operating Humidity: 5% RH to 95% RH (non-condensing) Storage Humidity: 5% RH to 95% RH (non-condensing)	
Weather Resistance	IP Rating: IP41 Lightning Protection/Surge Protection: ±2 kV	
Software		
Working Mode	Router Mode	YES
	AP Mode	YES
WLAN	Max. Number of SSIDs	8 per radio
	Band Steering	YES
	Wireless Meshing	YES
	Wi-Fi Multimedia (WMM)	YES
	802.1Q VLAN	YES
	Multi-Link Operation (MLO)	NO
	4K-QAM	NO



	RF Beamforming	YES
	WiFi Speed Limiting	YES
	Client Device Isolation	YES
	Wi-Fi Schedules	YES
Roaming	802.11v	YES
	802.11k	YES
	802.11r	YES
	Layer2 roaming	YES
	Layer3 roaming	YES
Security	PSK Authentication	YES
	WPA (TKIP), WPA2 (AES), and WPA-PSK	YES
	OWE (Enhanced Open) WPA3-SAE WPA2-PSK/WPA3-SAE	YES
	802.1X	YES
	Ping	YES
	Traceroute	YES
Routing	NAT	YES
	Static IP address	YES
	DHCP Server	YES
	PPPoE Client PPPoE Dial-up	YES
AP Mesh	Mesh Management	YES
Standalone Portal	Captive Portal	YES
	Bandwidth Limiting	YES
	Data Quota	No
Management and Maintenance	Number of APs on a Self-Organizing Network	300
	Unified Networking for All Network Equipment	YES
	Local or Remote Management through Lysora App	YES
	Local Management through the Web Interface	YES
	Remote Management through Lysora Cloud	YES
	SNMP	YES



Platform Management	Optimization of Channel, Transmit Power, and Management Frame Power Settings. Both Pre- and Pro-Optimization Settings are Displayed.	YES
Features	Unified Configuration or Monitoring through Lysora Cloud	YES
Compliance and Standard		
NDAA Complain	Yes	
Health	UL 62368-1:2019	
RF	FCC 47 CFR Part 2 Subpart J FCC 47 CFR Part 15 Subpart E IC RSS-247 Issue 3	
EMC	FCC 47 CFR Part 15 Subpart B ICES-003 Issue 7	
Certifications	FCC, IC	
Operating Frequency	US/CA: 2400 - 2472 MHz U-NII-1: 5150 - 5250 MHz U-NII-2A: 5250 - 5350 MHz U-NII-2C: 5470 - 5725 MHz U-NII-3: 5725 - 5850 MHz U-NII-5 to U-NII-8 : 5925 - 7125 MHz Worldwide: 2400 - 2483.5 MHz 5150 - 5725 MHz 5925 - 7125 MHz	



Lysoira



Deliver Intelligent Networks