


Network Video Recorder NVR504-E-IM Series



Features

- Support Ultra 265/H.265/H.264 video formats
- Support 16/32/64 channel input
- Support 3 ch HDMI, 1 ch VGA. HDMI up to 4K (3840x2160) resolution
- Support VGA and HDMI independent output
- Support up to 32 Megapixels resolution recording
- Support ANR technology to enhance the storage reliability when the network is disconnected
- Support cloud upgrade

Specifications

Model	NVR504-16E-IM		NVR504-32E-IM	NVR504-64E-IM
Decoding				
Decoding Format	Ultra 265, H.265, H.264			
Decoding Capability	Smart Off: H265/H264: 2 x 32MP@30, 4 x 16MP@30, 5 x 12MP@30, 8 x 4K@30, 10 x 6MP@30, 12 x 5MP@30, 16 x 4MP@30, 16 x 3MP@30, 16 x 1080P@30, 16 x 720P@30	Smart Off: H265/H264: 2 x 32MP@30, 4 x 16MP@30, 5 x 12MP@30, 8 x 4K@30, 10 x 6MP@30, 12 x 5MP@30, 16 x 4MP@30, 21 x 3MP@30, 32 x 1080P@30, 32 x 720P@30	Smart Off: H265/H264: 2 x 32MP@30, 4 x 16MP@30, 5 x 12MP@30, 8 x 4K@30, 10 x 6MP@30, 12 x 5MP@30, 16 x 4MP@30, 21 x 3MP@30, 32 x 1080P@30, 64 x 720P@30	
	Smart On: H265/H264: 1 x 32MP@30, 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 5 x 6MP@30, 6 x 5MP@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30, 16 x 720P@30	Smart On: H265/H264: 1 x 32MP@30, 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 5 x 6MP@30, 6 x 5MP@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30, 32 x 720P@30	Smart On: H265/H264: 1 x 32MP@30, 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 5 x 6MP@30, 6 x 5MP@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30, 32 x 720P@30	
Decoding Capability Description	The resolution of each channel cannot exceed 8192 pixels in length or width			
Audio Compression	G.711A, G.711U			
Network				
Incoming Bandwidth	Smart Off: 384 Mbps, Smart On: 200 Mbps			
Outgoing Bandwidth	Smart Off: 384 Mbps, Smart On: 200 Mbps			
Max Users Can Be Added	32			
Max Remote Users	128			
Protocols	TCP/IP, P2P, SMTP, NFS, 802.1x, RTSP, UPnP, NTP, DHCP, DNS, DDNS, SNMP, IPv6, IPv4, HTTPS, PPPoE, HTTP			
Browser (Plugin)	Chrome, Edge, Firefox			
Browser (Plugin-Free)	Chrome, Edge, Firefox, Safari			
Video/Audio Input				
IP Video Input	16-ch	32-ch	64-ch	
BNC Audio Input	N/A			
RCA Audio Input	1-ch			
3.5mm Audio Input	N/A			
Peripheral Input				
POS	All channels			
Ip Speaker	16-ch			
Video/Audio Output				
Video Output	Support 3-ch HDMI, 1-ch VGA, HDMI1 and VGA simultaneous output, HDMI1 /VGA and HDMI2 and HDMI3 independent output.			
HDMI Output	HDMI1: 4K (3840 2160)/60 Hz, 4K (3840 2160)/30 Hz, 1920 × 1080/60 Hz, 1280 × 720/60 Hz; HDMI2: 4K (3840 2160)/60 Hz, 4K (3840 2160)/30 Hz, 1920 × 1080/60 Hz, 1280 × 720/60 Hz; HDMI3: 4K (3840 2160)/60 Hz, 4K (3840 2160)/30 Hz, 1920 × 1080/60 Hz, 1280 × 720/60 Hz			


	4K (3840 2160)/30 Hz, 1920 × 1080/60 Hz, 1280 × 720/60 Hz;HDMI3:1920 × 1080/60 Hz, 1280 × 720/60		
VGA Output	1920 × 1080/60 Hz, 1280 × 720/60 Hz		
HDMI Standard	HDMI2.0		
BNC Audio Output	N/A		
RCA Audio Output	2-ch		
3.5mm Audio Output	N/A		
Liveview Display	HDMI1 and VGA: 1/4/6/8/9/16 HDMI2: 1/4/6/8/9/16 HDMI3: 1/4/6/8/9/16	HDMI1 and VGA: 1/4/6/8/9/16/25/32 HDMI2: 1/4/6/8/9/16 HDMI3: 1/4/6/8/9/16	HDMI1 and VGA: 1/4/6/8/9/16/25/36/64 HDMI2: 1/4/6/8/9/16/25/36 HDMI3: 1/4/6/8/9/16
Default Num of Live Screen	HDMI1 and VGA: 16; HDMI2: 16; HDMI3: 16	HDMI1 and VGA: 32; HDMI2: 16; HDMI3: 16	HDMI1 and VGA: 64; HDMI2: 36; HDMI3: 16
Corridor Mode Screen	HDMI1 and VGA: 3\4\5\7\9\10\12\16; HDMI2: 3\4\5\7\9\10\12\16; HDMI3: 3\4\5\7\9\10\12\16;	HDMI1 and VGA: 3\4\5\7\9\10\12\16\32; HDMI2: 3\4\5\7\9\10\12\16\32; HDMI3: 3\4\5\7\9\10\12\16;	HDMI1 and VGA: 3\4\5\7\9\10\12\16\32; HDMI2: 3\4\5\7\9\10\12\16\32; HDMI3: 3\4\5\7\9\10\12\16;
Playback Screen	1/4/9/16		
Corridor Mode Screen of Playback	1/3		
Two-way Audio			
Two-way Audio	1-ch, RCA (Using the audio input and output)		
Snapshot			
FTP/Schedule/Event Snapshot	16-ch snapshot (max. 8 MP (3840 × 2160) video resolution, with 1080P snapshot resolution)		
Recording			
Recording Resolution	32 MP/16 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080P/960P/720P/D1/2CIF/CIF		
Num of Concurrent Playback	32-ch		
Synchronous Playback in Local	16-ch		
Smart Function			
VCA Detection by IPC	Face Detection, Face Comparison, SIP (Intrusion Detection, Cross Line Detection, Enter Area, Leave Area), Ultra Motion Detection (UMD), Temperature Detection (Fire Detection, Smoking Detection, Temperature Measurement, Smoke and Fire Detection), People Counting (People Flow Counting, Crowd Density Monitoring), Video Metadata, Long Stay Detection, Fall Detection, Multi-Target Detection, Package Detection, Vehicle Detection (LPR)		
Smart by IPC	All channels (up to 16 images/s in total) Face Detection, Face Comparison, Vehicle Detection (LPR), Temperature Detection, SIP, UMD, Video Metadata, People Counting		
Smart by NVR	Face Detection, Face Comparison, Ultra Motion Detection (UMD), Smart Intrusion Prevention (SIP), Video Metadata, Plate Comparison		
Smart by NVR Analyzer Mode	Mixed Mode (Face Recognition+Mixed-Traffic Dection+AcuSearch/AcuTrack), Single Mode (SeekFree Mode), Mixed Mode (SIP+UMD), Modes cannot active simultaneously, only one mode		

	can active at a time.
VCA Search	Face Snapshot Search, Face Comparison Search, Motor Vehicle Search, Non-Motor Vehicle Search, General Search, People Counting Report, Heat Map, SmartSearch+, AcuSearch, AcuTrack, SeekFree, Pedestrian Search, Event Search
AcuSearch	
Acu Search Performance	All channels with UNV SIP/UMD Camera, Up to 4-ch with normal camera (UNV and Third-part brand, 4-ch 4K/5MP/4MP/3MP/2MP)
AcuTrack	
Acu Track Performance	All channels with UNV SIP/UMD Camera, Up to 4-ch with normal camera (UNV and Third-part brand, 4-ch 4K/5MP/4MP/3MP/2MP)
SeekFree	
SeekFree Performance	All channels with UNV SIP/UMD Camera
SeekFree Language	English
face detection	
face detection by NVR	Up to 16-ch with UNV Face Detection Camera, Up to 4-ch with normal camera (UNV and Third-part brand, 4-ch 4K/5MP/4MP/3MP/2MP)
Search by Image	Support
Plate Comparison	
Plate Comparion by NVR	All channels with UNV LPR Camera, normal/Third-part brand cameras not supported
Vehicle Number Library	Up to 16 vehicle picture libraries, with up to 25,000 vehicle pictures in total
SIP	
SIP by NVR with normal cameras	8-ch
UMD	
UMD by NVR with normal cameras	16-ch
analysis	
analysis with normal cameras	N/A
analysis Type	N/A
Video Metadata	
Video Metadata by NVR with normal cameras	Up to 4-ch with normal camera (UNV and Third-part brand, 4-ch 4K/5MP/4MP/3MP/2MP)
Video Metadata Type	Motor Vehicle: Vehicle Type, Vehicle Color, Vehicle Brand, Direction, Plate Type, Plate Color, Non-Motor Vehicle: Non-Motor Vehicle Type, Direction, Gender, Age, Upper Garment Length, Upper Garment Color, Human Body: Gender, Age, Mask, Hairstyle, Bag Style, Direction, Upper Garment Length, Lower Garment Length, Upper Garment Color, Lower Garment Color
Capacity of Smart Snapshots	
Intelligent Mark by IPC	Support
Capacity of Snapshot Records	3 millions records for face snapshot, 2 millions records for vehicle snapshot, 2 millions records for SIP, 2 millions records for Video Metadata
Alarm	
General Alarm	Defocus Detection, Scene Change Detection, Object Left Behind, Object Removed, Auto Tracking, Motion Detection, Tampering, Human Body Detection, Video Loss, Audio Detection, Alarm Input

Alert Alarm	IP Conflict, Network Disconnected, Disk Offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Array Damaged		
Num of Concurrent Processing Alarms	One every 5 seconds		
Hard Disk			
SATA	4 SATA Interfaces		
Capacity	Up to 24 TB for each HDD (The maximum HDD capacity varies with environment temperature and hard disk size, The environment temperature for use should not exceed 40°C.)		
Disk Group	Support		
Redundant Storage	Support		
Disk Array Type	RAID 0, 1, 5	RAID 0, 1, 5	N/A
Hot Swap	N/A		
External Interface			
Network Interface	2 RJ45 10 M/100 M/1000 M self-adaptive Ethernet Interface		
Network Working Mode	Multi-access, load balance, network fault-tolerance		
USB	Front panel: 2 × USB2.0, Rear panel: 2 × USB3.0		
RS485	1		
RS232	1		
Alarm In	16-ch		
Alarm Out	10-ch		
eSATA	1		
miniSAS	N/A		
miniSAS HD	N/A		
Power Output	12 V		
Extension Board	N/A		
Buzzer	Support		
Power Supply	AC 100 to 240 V		
Power Switch	N/A		
Redundant Power Supply	N/A		
PoE			
PoE Interface	N/A		
Max Power	N/A		
Supported Standard	N/A		
Working Environment			
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)		
Working Humidity	≤ 95% RH (non-condensing)		
Power Consumption (without HDD)	≤30W		
Heat Dissipation	Fan, Radiator		
Dimensions			
Weight (without HDD)	≤ 5.5kg (12.1lb)		
Height	2U		
Dimensions	442mm (17.4") x 432.9mm (17") x 88.6mm (3.5")		

GUI Language	
GUI Language	38 languages: Simplified Chinese, Traditional Chinese, English, Vietnamese, Thai, Turkish, Spanish (Latin America), Portuguese (Brazil), Spanish, Portuguese, French, German, Italian, Dutch, Polish, Czech, Hungarian, Slovak, Russian, Hebrew, Arabic, Ukrainian, Estonian, Bulgarian, Greek, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenia, Serbia, Korean, Japanese, Latvian, Lithuanian, Persian
Certification	
Certification	CE; FCC; UL; RoHS; WEEE
CE	EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 50130
FCC	Part15 Subpart B

Dimensions



Accessories

FL-2U		
Mount Angle Components,Sheetmatel		

Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2026 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.